

PM660

50 kVA ~ 800 kVA
PF 0.9



Highlights

Power flexibility from 50 kVA – 800 kVA

Modular hot-swappable & Scalability

High MTBF and low MTTR

High efficiency

High adaptability

EA660 modular UPS is ideal for reliable, saving, intelligent and easy solutions. It ensures that a scalable, secure, high quality power supply is available for any critical high – density computer and IT environment applications, such as data centers and other critical loads.

EA660 modular UPS is a scalable three–phase / three–phase uninterruptible power supply system with DSP technology and provides true on – line double conversion power protection. The available UPS power and redundancy level can expand vertically from 50 to 800 kVA / 720 kW in one single power cabinet, and four power cabinets can be connected in parallel, increasing the capacity up to 3.2 M kVA. It features modular hot–swappable design, all modules support “plug & play” , including power modules, bypass module, and control module, simplifies UPS servicing and maintenance.

Features

- DSP digital control technology
- Pure sine wave double conversion, with strong load capacity
- Flexible modularity and easy scalability with all hot–swappable module design
- High efficiency at low load rate: 96% at 40% rated load and 95% at 20% rated load
- High power density of 50 kVA / 3U power module
- High grid adaptability, strong load adaptability and strong overload capability
- Small footprint (500 kVA system only 1.02 m² footprint)
- Inbuilt integrated PDU system, easy installation and saving investment
- Input power factor > 0.99, THDi < 3%, environment friendly and high – efficiency and energy – saving
- Wide input voltage range, 50 Hz / 60 Hz frequency auto–sense, adapt to all kinds of grid
- Soft–start technology improves generator matching up to 1:1.1
- Support two modes of frequency conversion: 50 Hz input / 60 Hz output and 60 Hz input / 50 Hz output
- Intelligent hibernation design enables UPS to operate efficiently at low load rate
- Advanced parallel expansion technology, support 4 units in parallel
- Share battery pack in parallel operation, saving user's battery cost
- Flexible charger parameter and battery configuration setting, numbers of battery 30 ~ 46 pcs selectable
- Intelligent battery management (Intelligent charge/discharge management and float charging voltage temperature compensation), extending battery lifespan
- Support battery cold start and utility self boot
- Self–aging function, easy debugging and test on site
- Fault–tolerant design for fan system: 30% load can be driven when 2 fans fail and 50% load when 1 fan fails
- Front accessible maintenance, top/bottom cable entry compatible
- Complete hardware and software protection function, robust self – diagnostic function, and abundant event log for check
- 7 inches LCD touch screen, friendly human – machine interface
- Monitoring unit with built–in SNMP, supports RS485 and dry contacts

